



SIGN - Permit Application

SUBJECT PROPERTY INFORMATION		
Property Address	703 Wilcox Street Suite J	
Property Lot and Block Legal Description, if available	LOTS 11-12 BLK 11 WILCOX ADDITION 0.320 AM/L RLTD 0475673	
Business or Property Name (e.g. Uptown Lofts)	Fulcrum Academy	
Property Zone District B in Downtown Overlay	<input type="checkbox"/> Residential <input checked="" type="checkbox"/> Business/Commercial <input type="checkbox"/> Planned Development <input checked="" type="checkbox"/> Overlay District Commercial Downtown	
Property Owner Base of The Rock LLC	Name: John Shepherd	Phone: 623-693-6761
	Street: 1864 Woodmoor Dr STE 205	City: Monument, CO
	Email: johnshepherd@tglinvestments.com	Zip: 80132
APPLICANT INFORMATION (IF NOT PROPERTY OWNER)		
Title or Interest in property and building, check one	<input type="checkbox"/> Lessee <input type="checkbox"/> Agent <input type="checkbox"/> Contractor	
Applicant YESCO LLC	Name: Chuck Boncordo	Phone: 303-246-4300
	Street: 11220 E 53rd Ave #300	City: Denver
	Email: cboncordo@yesco.com	Zip: 80239
Sign Contractor YESCO LLC	Name: Chuck Boncordo	Phone:
	Street: 11220 E 53rd Ave #300	City: Denver
	Email: cboncordo@yesco.com	Zip: 80239
Electrical Contractor Genesis One Three Electric	Name: Dustin	Phone: 303-88306562
	Street: 7344 S Alton Way Suite B	City: Centennial
	Email: Dustin@genesiselectricaldenver.com	Zip: 80112
PROPOSED SIGN(S)		
Description of Work	Install one roof mounted sign per YESCO Design ART40344R2	
Type of Sign(s) Roof	<input checked="" type="checkbox"/> Permanent Sign <input type="checkbox"/> Temporary Construction Sign	
Sign Text	FULCRUM ACADEMY with Logo	
If Temporary Sign, dates of display	From ____ / ____ / ____ To ____ / ____ / ____	
Estimated Installation Date	9 / 25 / 2021	
Type of Sign(s)	<input type="checkbox"/> Wall* <input type="checkbox"/> Window <input type="checkbox"/> Ground (Free-standing/ Monument)* <input type="checkbox"/> Marquee/Arcade* <input type="checkbox"/> Projecting* <input type="checkbox"/> Canopy/Awning* <input type="checkbox"/> Construction Sign <input checked="" type="checkbox"/> Mural/Roof Sign* Design Review Board Approval# <u>TBD</u> <input type="checkbox"/> Other _____	
	Sign Height: 14.5' _____ Feet	
	* Building Plan Review May be Required	



SIGN - Permit Application (Continued)

Face	<input checked="" type="checkbox"/> Single Face <input type="checkbox"/> Double Face	Illumination Internal	<input checked="" type="checkbox"/> Yes (Building Review Required) <input type="checkbox"/> No
Awnings backlit? No	<input type="checkbox"/> Yes (Building Review Required) <input type="checkbox"/> No	If yes for Illumination, is the light source concealed?	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
VALUATION			
Estimated Value (to the nearest dollar): \$ 8,974.00 .00			
ATTACHMENTS			
Required to submit all of the following (see submittal checklist for more detail):	<input checked="" type="checkbox"/> Site Plan <input checked="" type="checkbox"/> Sign Depiction or Photo Simulation <input checked="" type="checkbox"/> Building Elevations showing signage - existing and proposed <input checked="" type="checkbox"/> Structural Drawings/Calculations <input checked="" type="checkbox"/> Connection and structural details <input type="checkbox"/> Electrical Plans (if Illuminated) <input type="checkbox"/> Encroachment Permit (If Required)		
SITE INFORMATION			
Number	Area in Square Feet	Type	
Signs Removed	1	Unknown	
Existing Signs to Remain	0		
Proposed Sign(s)	1	55.94	
TOTAL APPROVED		n/a	
TOTAL Permitted/Allowed	1	58.5	
Balance	0	2.56	
SIGNATURE REQUIRED			
I hereby certify that, to the best of my knowledge and belief, all information supplied in this application is true and accurate.			
Applicant Signature <u>Chuck Boncordo</u>			
Full Name (Print) <u>Chuck Boncordo</u>	Date <u>08/04/2021</u>		
Property Owner Signature _____			
Full Name (Print) <u>See attached email dated 7/12/2021</u>	Date _____		

FEES: \$50.00 Each Sign plus building permit fees based on valuation



SIGN - Permit Application (Continued)

Sign Permit Checklist:

Application for Sign Permit

Site Plan

Provide a dimensioned site plan depicting the location of all structures, existing signs and proposed sign(s) on the subject property.

The proposed sign shall include dimensions from zone lot lines, height dimensions, etc. The Site Plan boundary shall include any streets, alleys, and property lines.

Sign Depiction or Photo Simulation

Provide a dimensioned drawing of the sign(s), including copy and any other details

Building Elevation showing signage

Provide an elevation of the sign as it will appear on building facade, including any existing, to remain signs

Staff may need to request additional information depending on the project

Property owner signature on application, affidavit or approval on sign plans

Encroachment Permit

A right-of-way encroachment permit application shall accompany the sign permit application if the sign extends across a public right-of-way or public easement (such as in the case of a projecting sign or freestanding sign). The applicant shall provide evidence of adequate liability insurance as required by the Town of Castle Rock.

For Signs requiring Building Permit, a licensed contractor shall submit:

Structural Drawings/ Structural Calculations


Plans indicating the scope and structural detail of the work to be done, including details of all connections, guy lines, supports, footings and materials to be used.

Electrical Plans YESCO LLC is not responsible for electrical on this project


Any additional drawings provided by manufacturer




SIGN - Permit Application (Continued)




JOINT IDENTIFICATION SIGN




MONUMENT SIGN




WALL SIGN




WINDOW SIGN




AWNING SIGN




PROJECTING SIGN



CANOPY SIGN



MARQUEE SIGN



BLADE SIGN



Sheldon Marshall <smarshall@yesco.com>

RE: Fulcrum Academy sign**johnshepherd tginvestments.com <johnshepherd@tginvestments.com>**

Mon, Jul 12, 2021 at 6:48 PM

To: Evan Barrett <evan@fulcrumjiujitsuacademy.com>, "smarshall@yesco.com" <smarshall@yesco.com>**Cc: "dustin@genesiselectricaldenver.com" <dustin@genesiselectricaldenver.com>**

As the Managing Agent for Base or the Rock LLC (owning entity of 703 Wilcox), I approve of installation of the proposed sign as it is described in the attached pdf for Fulcrum Jiu Jitsu Academy.

John Shepherd

TGL Investments LLC

Managing Agent for Base of the Rock LLC (also an owning member of Base of the Rock LLC)

1864 Woodmoor Dr, Ste 205

Monument CO 80132

Ph 623-693-6761

johnshepherd@tginvestments.com

Units leased: A, B, J, K & L

703 Wilcox St

Owner LV Approve

John Shepherd



From: Evan Barrett <evan@fulcrumjiujitsuacademy.com>
Sent: Monday, July 12, 2021 6:10 PM
To: johnshepherd tginvestments.com <johnshepherd@tginvestments.com>
Subject: Fwd: Fulcrum Academy sign

Hey John, can you send him an email saying that you approve this design?

Sent from my Verizon, Samsung Galaxy smartphone
Get [Outlook for Android](#)

Structural Engineering Calculations for:

Fulcrum Jiu Jitsu Academy, OPY-40344

703 Wilcox St
Castle Rock, CO

Raceway Letters on Brackets

Index

Title	1
Basis for Design	2
Wind Loads	3
Snow Loads	4-5
FEA	6-15
S-5! Installation Instructions	16-17
Drawing	Attached

Prepared by: Dave Knight

7/30/2021

Reviewed by: Ben Jones



BASIS FOR DESIGN

Project: Fulcrum Jiu Jitsu Academy, OPY-40344

Descript: *Raceway Letters on Brackets*

BUILDING CODE:

2018 EDITION OF THE INTERNATIONAL BUILDING CODE

APPROXIMATE SITE ELEVATION:

GROUND ELEVATION = **6179 FT**

LIVE / SNOW LOADS: NA

GRAVITY / DEAD LOADS:

RACEWAY LETTERS 5 PSF

LATERAL LOAD PARAMETERS:

RISK CATEGORY = **II**

WIND:

BASIC WIND SPEED, V = **107 MPH, 3-SECOND GUST**

WIND EXPOSURE = **C**

SEISMIC: < WIND, WIND GOVERNS

STEEL:

PLATES AND SHAPES: *ASTM A36*, $F_y = 36$ ksi

WELDING: LOW HYDROGEN, E70 SERIES RODS

BOLTS: *ASTM F3125, GRADE A325*

FABRICATION AND ERECTION TO COMPLY WITH LATEST AISC SPECIFICATIONS.



ENGINEERING
www.yesco.com

JOB NAME FULCROM ACADEMY
LOCATION CASTLE ROCK, CO

DATE 7/30/2021 BY DK

OPY# 40344

F:\Jobs 2021\Yesco\Fulcrum Jiu Jitsu Academy, Castle Rock, CO OPY-40344\Fulcrum Jiu Jitsu Academy, Castle Rock, CO OPY-40344.dwg

ASCE 7-16, Wind Pressure

Chapter 29: Wind Loads on Building Appurtenances and Other Structures: MWFRS (Directional Procedure)

Section 29.5 Parapets:

Refer to Section 27.3.5 for buildings of all heights using the directional Procedure. Note, parapets are actually referenced in Section 27.3.4. Typo assumed.

Section 27.3.4 Parapets:

$$p_p = q_p (Gc_{pn}) \text{ (Eq. 27.3-3)}$$

$$q_p = 0.00256 k_h k_{zt} k_d k_e V^2 \text{ (Eq 26.10-1)}$$

•• $\alpha = 7.0$ (Exp. B) = 9.5 (Exp. C); (Table 26.11-1)

•• $z_g = 1200$ (Exp. B) = 900 (Exp. C); Table 26.11-1)

•• $K_h \& K_z = 2.01(15 / z_g)^{2/\alpha}$, (Table 26.10-1, $z < 15\text{ft}$)

•• $K_h \& K_z = 2.01(z / z_g)^{2/\alpha}$ (Table 26.10-1, $15\text{ft} \leq z \leq z_g$)

•• (Note: $z = 14.67\text{ ft}$, Exp. C)

• $K_h = 0.85$ ($h \approx 14.67\text{ ft}$)

•• $K_z = 0.85$ ($z \approx 14.67\text{ ft}$)

• $K_{zt} = 1.00$ (26.8.2)

• $K_d = 0.85$ (Table 26.6-1)

• $K_e = e^{-0.0000362 * z_g}$

•• Ground Elev, $Z_g = 6179\text{ ft}$

• $K_e = 0.80$ (Table 26.6-1)

• $V = 107\text{ mph}$

$q_p = 16.94\text{ psf} (> 16\text{ psf})$ O.K.

$$Gc_{pn} \text{ (windward Parapet, positive)} = 1.5 \text{ (27.3.4)}$$


$$Gc_{pn} \text{ (leeward Parapet, negative)} = -1.0 \text{ (27.3.4)}$$

$$p_p \text{ (Windward Parapet positive)} = (16.94\text{ psf})(1.5) = +25.41\text{ psf}$$

$$p_p \text{ (Leeward Parapet negative)} = (16.94\text{ psf})(-1.0) = -16.94\text{ psf}$$

BALANCED AND UNBALANCED SNOW LOAD ON GABLE AND HIP ROOFS

ASCE 7-16, Figure 7.6-2



Reduction for Adjacent Structures and

Terrain Features Within 20 ft (7.7.2):

s = separation distance (ft) = (> 20 ft)

h = height difference between upper & lower roof

$h = 0 \text{ ft}$

$6h = 0 \text{ ft}$

If $s < 20'$ and $s < 6h$, See Section 7.7.2

No reduction in this case.

Balanced Snow Load (Fig 7.6-2):

$p_{\text{balanced}} = p_s = 35 \text{ psf}$

Unbalanced Load (Section 7.6.1):

For Hip and Gable roofs with a slope exceeding 7 on 12 or less than $\frac{1}{2}$ on 12 , unbalanced snow loads are not required:

Actual Slope = 12 on 12 , unbalanced Not Required.

For $W \leq 20 \text{ ft}$, with Simply supported prismatic members spanning from ridge to eave, shall be designed to resist an unbalanced snow load on the leeward side (windward side is unloaded):

$p_{\text{unbalanced}} = I_s * p_g$

$p_g = 35 \text{ psf}$


$I_s = 1.0$ (Table 1.5-2, Cat. II)

$p_{\text{unbalanced}} = (1.0)(40 \text{ psf}) = 35 \text{ psf}$ Not Required.

For all other roofs, the unbalanced load shall consist of $0.3P_s$ on the windward side, P_s on the leeward side plus a rectangular surcharge with magnitude $h_d \gamma / \sqrt{S}$ with magnitude $(8/3) h_d \sqrt{S}$ Not Required.

SNOW DRIFT ON ROOF PROJECTIONS (RE: SNOW DRIFT ON LOWER ROOFS)

ASCE 7-16, Figure 7.7-2



Snow Drift on Parapet (Sign) Section 7.8 (Refer to Section 7.7.1):

Given:

$Y \approx 3.65$ ft (Height that Sign extends above eave)

$P_g = 35$ psf

$\gamma = 0.13 P_g + 14$ (but not more than 30 pcf) (Eq. 7.7-1) = 18.55 pcf

h_b (height of balanced snow load) = $P_g / \gamma = 35$ psf / 18.55 pcf = 1.89 ft

h_c = Max From T.O. Balanced Snow Load

- 1) closest point on adjacent upper roof
- 2) T.O. parapet
- 3) T.O. roof projection

h_c (per #2 above) = $Y - h_b = 1.76$ ft

Check if: $h_c / h_b < 0.2$: $1.76 / 1.89 = 0.93 > 0.2$, therefore drifting considered

Length of roof upwind of the wall (sign), $l_u = 5.33$ ft < 20 ft

therefore use $l_u = 20$ ft

$h_d = [0.43((l_u)^{1/3})((P_g + 10)^{1/4}) - 1.5] * \sqrt{l_u}$ (Fig 7.6-1)

$h_d = 1.52$ ft

But not greater than: $\sqrt{l_u P_g l_u / 4 \gamma}$, Where l_u equals actual l_u

not the minimum fetch distance of 20 ft

$h_d = 1.58$ ft

Use $0.75 h_d = 0.75 * 1.52$ ft = 1.14 ft

Height of Snow, $h = (h_b + h_d) = 1.89 + 1.14 = 3.03$ ft ≈ 36 in

Lateral Load on Parapet (Sign):

(per "Snow Loads, Guide to the Snow Load Provisions of ASCE 7-05" by Michael O'Rourke)

$$K^a = [1 - \sin \theta] / [1 + \sin \theta]$$

Where θ = angle of repose (internal angle of friction)

Typical values for fresh fallen snow, $\theta = 50^\circ$ to 60°

Typical values for wind blown snow, $\theta = 6^\circ$ to 26°

Use $\theta = 15^\circ$

$$K^a = [1 - \sin 15^\circ] / [1 + \sin 15^\circ] = 0.59$$

$$\text{Lateral Pressure, } P_t = K^a \gamma_{mid} h_b$$

Where Mid Height of Snow, $h / 2 = 18$ in

$$K^a = 0.59$$

$$h = 3.03 \text{ ft}$$

$$\gamma_{mid} = 17.5 \text{ pcf (Figure VII-5)}$$

$$P_t = 31 \text{ psf}$$








Figure VII-5 Snowpack density versus snowpack depth as per ASCE 7-05 as per Equation 7-3.



YESCO, LLC
Dave Knight
OPY-40344

Fulcrum Academy
Model



July 30, 2021 at 2:55 PM
Fulcrum Jiu Jitsu Academy, Castle...



YESCO, LLC
Dave Knight
OPY-40344

Fulcrum Academy
Boundary Nodes, Members and Nodes


July 30, 2021 at 3:02 PM
Fulcrum Jiu Jitsu Academy, Castle...





YESCO, LLC
Dave Knight
OPY-40344

Fulcrum Academy
Member Shapes



July 30, 2021 at 3:03 PM
Fulcrum Jiu Jitsu Academy, Castle...







Loads: BLC 2, WL(LW)

YESCO, LLC	Fulcrum Academy Leeward Wind Load (32" Trib. Width)	
Dave Knight		July 30, 2021 at 3:05 PM
OPY-40344		Fulcrum Jiu Jitsu Academy, Castle...





Loads: BLC 3, WL(WW)

YESCO, LLC	Fulcrum Academy Windward Wind Load (32" Trib. Width)	
Dave Knight		July 30, 2021 at 3:05 PM
OPY-40344		Fulcrum Jiu Jitsu Academy, Castle...



Loads: BLC 4, SL

YESCO, LLC	Fulcrum Academy Lateral Snow Load (32" Trib. Width)	
Dave Knight		July 30, 2021 at 3:06 PM
OPY-40344		Fulcrum Jiu Jitsu Academy, Castle...



Member Code Checks Displayed (Enveloped)
Envelope Only Solution
Reaction and Moment Units are lb and k-ft (Enveloped)

YESCO, LLC	Fulcrum Academy Unity Bending Check (All Members are > 0.5)	
Dave Knight		July 30, 2021 at 3:07 PM
OPY-40344		Fulcrum Jiu Jitsu Academy, Castle...

Hot Rolled Steel Properties

Label	E [ksi]	G [ksi]	Nu	Therm (/1E5 F)	Density [lb/ft^3]	Yield [ksi]	Ry	Fu [ksi]	Rt
1	A992	29000	11154	.3	.65	490	50	1.1	65
2	A36 Gr.36	29000	11154	.3	.65	490	36	1.5	58
3	A572 Gr.50	29000	11154	.3	.65	490	50	1.1	65
4	A572 Gr.65	29000	11154	.3	.65	490	65	1.1	80
5	A500 Gr.B R...	29000	11154	.3	.65	527	42	1.4	58
6	A500 Gr. C R...	29000	11154	.3	.65	527	46	1.4	62
7	A500 Gr.B R...	29000	11154	.3	.65	527	46	1.4	58
8	A500 Gr. C R...	29000	11154	.3	.65	572	50	1.4	62
9	A53 Gr.B	29000	11154	.3	.65	490	35	1.6	60
10	A1085	29000	11154	.3	.65	490	50	1.4	65
11	A513	29000	11154	.3	.65	490	32	1.5	45

Hot Rolled Steel Section Sets

Label	Shape	Type	Design List	Material	Design R...	A [in2]	Iyy [in4]	Izz [in4]	J [in4]
1	Bracket	L2x2x3	Beam	Single Angle	A36 Gr.36	Typical	.722	.271	.271
2	Tie	Plate 3/16 x 2	Beam	BAR	A36 Gr.36	Typical	.375	.001	.125

Basic Load Cases

BLC Description		Category	X Gra...	Y Gra...	Z Gra...	Joint	Point	Distrib...	Area(Memb...	Surface(Plate/Wall)
1 DL		DL			-1			1		
2 WL(LW)		WL						1		
3 WL(WW)		WL						1		
4 SL		SL						1		


Load Combinations

Description	Solve	PDel...	SR...	B...	Fa...	BLC Fa...	BLC Fa...	B...	Fa...										
1 DL	Yes	Y		1	1														
2 DL+0.6WL(LW)+SL	Yes	Y		1	1	2	.6			4	1								
3 DL+0.6WL(WW)	Yes	Y		1	1			3	.6										

Joint Reactions (By Combination)

LC	Joint Label	X [lb]	Y [lb]	Z [lb]	MX [k-ft]	MY [k-ft]	MZ [k-ft]
1	2	N2	163.239	132.904	-1.621	NC	0
2	2	N1	180.284	-72.867	1.621	NC	0
3	2	Totals:	343.523	60.037	0		
4	2	COG (in):	X: -2649.548	Y: 3926.703	Z: 0		

↑
 Worst Case Load Combination (#2)



Results for LC 2, DL+0.6WL(LW)+SL
Reaction and Moment Units are lb and k-ft

YESCO, LLC	Fulcrum Academy Reactions	July 30, 2021 at 3:10 PM Fulcrum Jiu Jitsu Academy, Castle...
Dave Knight		
OPY-40344		



The right wayTM to attach almost anything to metal roofs!

Installation Instructions

S-5!® Warning! Please use these products responsibly! Visit our website or contact your S-5! distributor for available load test results. The user and/or installer of these parts is responsible for all necessary engineering and design to ensure the S-5! clamps have been properly spaced and configured. **Notice to S-5! users:** Due to the many variables involved with specific panel products, climates, snow melt phenomena, and job particulars, the manufacturer cannot and does not express any opinions as to the suitability of any S-5! assembly for any specific application and assumes no liability with respect thereto. S-5! products are tested for ultimate holding strength on various profile types and materials. Visit www.S-5.com for more details. This document is an installation guide only and the photographs and drawings herein are for the purpose of illustrating installation, tools and techniques, not system designs. Information contained within is intended to apply to the document as a whole.

The S-5-U, S-5-S, S-5-E, S-5-B, and S-5-V clamps are made for standing seam profiles. For horizontal seam applications, the setscrew(s) must be accessible from the top for tightening. S-5-U clamps have two bolt holes to accommodate either vertical or horizontal seam applications; visit www.S-5.com for more details.

Tools Needed

- Screw Gun*
- T30 Torx Bit Tip (provided)
- Dial-Calibrated Torque Wrench
(For accurate tension values, do NOT use a clicking torque wrench; inquire with S-5! for proper tool sourcing)

To Install the S-5-U, S-5-S, S-5-E, S-5-B, and S-5-V

1. Partially thread the setscrews into the clamp by hand. (The S-5-U has four setscrew locations to make the clamp more versatile; however, only two setscrews are used per clamp. Both setscrews should always be loaded into the same side of the clamp.)
2. Determine how to position the clamp. When attaching to machine-folded seams (regardless of panel profile and geometry), S-5! clamps are designed to engage the seam as shown in Illustration A; with setscrew opposite seam fold. On many snap-together type seams, the setscrews are on the open (or overlap) side of the seam. On some seams, this aspect of clamp orientation is not critical.
3. Tighten the setscrews using a screw gun* and the included screw gun bit tip. Setscrews should be tensioned and re-tensioned as the seam material compresses, i.e. tighten the first setscrew, then the second; then repeat until each setscrew achieves the recommended torque. The setscrews will dimple the seam material but will not penetrate it. When relying on published load values, setscrew tension should be verified periodically using a calibrated torque wrench as indicated below to ensure the tool is consistently achieving the proper torque range. **Note:** See "Step 3 Note" at bottom of document on fitting S-5-U and S-5-V on certain vertical double-folds.


* For time-saving tool recommendations, call S-5!

Specified Torque	Inch Pounds	Foot Pounds	Nm
22ga steel	160-180	13-15	18-20
All other metals and thinner gauges of steel	130-150	11-12.5	15-17


Once installed correctly, these clamps require no maintenance or re-inspection for the life of the roof.

4. For critical attachment applications utilizing an M8-1.25 X 16 mm Hex Flange Bolt, tighten the included M8 bolt to 160 inch pounds (13 foot pounds).

These instructions are for use by those experienced in the trade. Always follow appropriate safety precautions and use appropriate tools.



Above illustrations show S-5-U clamp on a vertical seam. Step 2 shows both vertical and horizontal applications.



(Top) S-5-U clamp on both vertical and horizontal seams.
(Bottom) S-5-S on a snap together seam with blow up illustrating deformation of seam as setscrew is tightened
For horizontal seams equal to or greater than .65" use the S-5-U in its horizontal orientation.
For horizontal seams equal to or less than .50" use the S-5-S mounted vertically.

S-5-U Mini, S-5-S Mini, S-5-E Mini, S-5-B Mini, and S-5-V Mini Installation Instructions

To Install the S-5-U Mini, S-5-S Mini, S-5-E Mini, S-5-B Mini, and S-5-V Mini

1. Partially thread the setscrew into the clamp by hand.
2. Determine how to position the clamp. When attaching to machine-folded seams (regardless of panel profile and geometry), S-5!® clamps are designed to engage the seam as shown in Illustration A on the front page; with setscrew opposite seam fold. On many snap-together type seams, the setscrew is on the open (or overlap) side of the seam. On some seams, this aspect of clamp orientation is not critical.
3. Tighten the setscrew using a screw gun* and the included screw gun bit tip. The setscrew will dimple the seam material but will not penetrate it. When relying on published load values, setscrew tension should be verified periodically using a calibrated torque wrench as indicated below to ensure the tool is consistently achieving the proper torque range. **Note:** See "Step 3 Note" at bottom of document on fitting S-5-U Mini and S-5-V Mini on certain vertical double-folds.


*For time-saving tool recommendations, call S-5!

Specified Torque	Inch Pounds	Foot Pounds	Nm
22ga steel	160-180	13-15	18-20
All other metals and thinner gauges of steel	130-150	11-12.5	15-17

Once installed correctly, these clamps require no maintenance or re-inspection for the life of the roof.

4. For critical attachment applications utilizing an M8-1.25 X 16 mm Hex Flange Bolt (sold separately), tighten the bolt to 160 inch pounds (13 foot pounds).

Step 3 Note: When installing S-5-U, S-5-V, S-5-U Mini, or S-5-V Mini on a vertical double fold, you may need to lift clamp in a manner that allows the lip of the clamp to engage the bottom of the seam and the setscrew(s) to fully engage the fold while tightening the setscrew(s). See clamp lip engagement in figure below. This will assist in making the clamp sit more vertically on the seam.



NOTE: Any S-5! warranty and/or calculation may be void if hardware is used that was not furnished by S-5! directly or through one of their licensed distributors


S-5!® Warning! Please use this product responsibly!

Products are protected by multiple U.S. and foreign patents. Visit the website at www.S-5.com for complete information on patents and trademarks. For maximum holding strength, setscrews should be tensioned and re-tensioned as the seam material compresses, i.e. tighten the first setscrew, then the second; then repeat until each setscrew achieves the recommended torque. Clamp setscrew tension should be verified using a calibrated torque wrench between 160 and 180 inch pounds when used on 22ga steel, and between 130 and 150 inch pounds for all other metals and thinner gauges of steel. Consult the S-5! website at www.S-5.com for published data regarding holding strength.

Copyright 2020, Metal Roof Innovations, Ltd. S-5! products are patent protected.

S-5! aggressively protects its patents, trademarks, and copyrights. Version 040820.

USEBVI-V1.2-0420



Above illustrations show S-5-E Mini clamp on a vertical seam. Step 2 shows S-5-E Mini on vertical applications and S-5-U Mini on horizontal applications.



ENGINEERING

www.yesco.com

© 2020 YESCO LLC, All rights reserved

Revisions

No.	Date
Orig.	7/30/2021
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
	
<img alt="triangle icon" data-bbox="111 92	



Drawn by DAVE KNIGHT

Checked by **BEN JONES**

FULCRUM JIU JITSU ACADEMY

703 WILCOX ST
CASTLE ROCK, CO





Account Exec..... SHELDON MARSHALL
Designer..... KEVIN LANGFORD

Date: 7/30/2021


Project No.

OPY-40344

S1



AERIAL PHOTO



YESCO®

Denver Region

Denver
220 E. 53rd Avenue, Suite 300
Denver, CO 80239
303-375-9933

Colorado Springs
5011 List Drive
Colorado Springs, CO 80919
719-385-0104

This drawing was created to assist you in visualizing our proposal. The original ideas herein are the property of YESCO. Permission to copy or revise this drawing can only be obtained thru a written agreement with YESCO.

© 2021 YESCO LLC
All rights reserved
www.yesco.com

Scrum Jiu Jitsu Academy

RESS:

/ STATE / ZIP:

OUNT EXECUTIVE:
ELDON MARSHALL

GNER:

FINAL DATE:
01 2021

CUSTOMER APPROVAL

Client Signature / Date

Landlord Signature / Date

ICAL NOTE
: UNLESS OTHERWISE NOTED, ELECTRIC
S OR FINAL ELECTRICAL CONNECTIONS
ES ARE NOT INCLUDED. ILLUMINAT
AYS WILL BE WIRED FOR 120 VOLT POW
S OTHERWISE INDICATED.

SS OTHERWISE INDICATED.
TAGE IS NOT 120 PLEASE INDICATE YOUR VOLTAGE H

VOLTS **AMPS**

NOTE
 YESCO IS A UL LISTED
SIGN MANUFACTURER
SIGN IS INTENDED TO BE INSTALLED
ORDANCE WITH THE REQUIREMENTS
CICLE 600 OF THE NATIONAL ELECTRICAL CO-
DE OR OTHER APPLICABLE LOCAL CODES. TH-
ESES PROPER GROUNDING AND BONDING

SECTION NOTES

DATE	REVISION	DESIGN
7.21	NO CHANGE	KEVIN
12.24	NO CHANGE	KEVIN

DESIGN NUMBER:

ANT-4004-412

PAGE 1

